

Date 8/3/2023  
Revision C

### NOTES

1	Shimming is probably required for perfect scope alignment.
2	Rear base may require modifications for correct fit to military actions.
3	Front base may require modification for correct fit.
4	Gun will have to be drilled and tapped.
5	Front base screws must be shortened by grinding.
6	May require bolt and/or safety alteration, otherwise firearm cannot function safely and properly. Consult with a qualified gunsmith.
7	Base DOES NOT FIT Rossi Large Frame Matched Pair Combos. (All models with 12 GA or 20 GA barrels.)
8	Remove rear sight to use.
9	The handiest way to pinpoint the correct base for the Win. 52 & Win. 70 Long action Rifles is to check the spacing of the tapped holes for the rear base and compare it to the hole spacing for the front base. Does it have: HOLE SPACING THE SAME: Model 52: use 46+ 46, Model 70: use 47+ 46 HOLE SPACING DIFFERENT: Model 52: use 25+ 57 Model 70: use 49A+ 46
10	The Weaver type base built into this rifle will accept Weaver rings but our highest ring (1" See-Thru #49513) still isn't high enough to clear the front sight.
11	The Weaver type base built into this firearm will accept any Detachable Top Mount Weaver Ring.
12	Rifle has Grooved Receiver for Tip-Off Rings.
13	Ruger Mark II Pistols. Weaver only offers a clamp on base with 1" rings (Pistol Mount System #306). Ruger supplies a short or long base and 1" or 30mm rings w/factory drilled and tapped pistols. Contact Ruger at 602-778-6555 for these items.
14	Bolt Clearance problem may exist and scope will not be centered.
15	Base accepts Tip-Off Rings only.
16	TO-9, TO-10 & TO-11 bases accept either Detachable Top Mount Rings or Tip-Off Rings. Each have crossbolt slots and 3/8" grooves for both applications.
17	Must be factory drilled and tapped.
18	One-Piece base attaches to barrel and extends back over receiver.
19	Requires the use of Thompson/Center base adapter.
20	Requires drilling and tapping 4 holes in receiver and relief space cut in stock to clear base.
21	Rear base is positioned on top of receiver and front base is positioned on the barrel. Drilling & tapping required. One-piece base mounts w/2 set screws & newer guns are factory drilled & tapped.
22	For shorter tube scopes or red dot scopes use #402 extension front base or one-piece base if available. Extension base allows an extra .689".
23	WARNING: NOT FOR USE WITH X-FRAME REVOLVERS. USE ON FIREARMS OTHER THAN THOSE LISTED ABOVE MAY CAUSE INJURY.
24	Top mount base is designed to fit 12GA models only.
25	Can be used with Tactical Multi Slot Bases.
26	Rear Base Screws must be shortened by grinding.
27	Not available or discontinued.
28	Tactical Extended Multi-Slot Bases have 20 MOA versions as well.
29	Savage changed the Axis receiver threads from 6-49 to 8-40 in June of 2021. To identify what threads, Savage Arms added a drill point on the receiver. The drill point is located on the left side of the ejection port. If there is a drill point then the receiver has 8-40 threads, if no drill point, then the receiver has 6-48 threads.













WEAVER™ MOUNT APPLICATIONS CHART	N O T E S	WEAVER™ ALUMINUM TOP MOUNT BASES						MULTI-SLOT BASES		STEEL LOCK SEE THRU RINGS	Complete Mount Systems	SIDE MOUNT	GRAND SLAM™ STEEL TOP MOUNT BASES				GRAND SLAM™ DOVETAIL BASES	
		STANDARD 2-PC BASES			EXTENSION BASES		1-PC	1-PC	1-PC				STANDARD		EXTENSION		1-PC	2-PC
		REAR	FRONT	Base Pairs	REAR	FRONT	1-PC	Multi-Slot Bases	Extended multi-slot bases				No Bases Required	Bases w/Rings	USE ONLY WITH SIDE MT BRACKET	REAR	FRONT	REAR
472, 479 & 679						80 (48080)												
464 Lever Action (Center Fire Only)		403 (48107)	403 (48107)															
4X4		35 (48035)	36 (48036)															
- Matte		35M (48500)	36M (48501)	48460														
- Silver		35S (48006)	36S (48005)	48461														
500AS (Pre 1997) & 600 Shotguns						88 (48088)												
500 (1997+) 510, 590, 535 & 835 Shotguns (matte)				48473		417M (48440)	417T (48333)											
810 & RM7		25 (48025)	11 (48011)															
100 ATR, 1500, 1700		36 (48036)	36 (48035)			40A (48040)										48912	48900	
- Matte		36M (48501)	35M (48500)	48460		40AM (48428)			49712			S36 (48225)	S35 (48224)	S40A (48243)	48913	48901		
- Silver		36S (48005)	35S (48006)			40A-S (48041)												
930,935 (Matte)						430M (48455)												
9200						430 (48455)												
Mossberg SSA . MVP 5.56/224VLK																		
- Matte		650	35M (48500)	48483		40AM (48428)		99467				S36 (48225)	S35 (48224)					
Patriot S/A, MVP 7.62/6.5cm																		
- Matte		650	35M (48500)	48483		40AM (48428)	615 (48318)	99475				S36 (48225)	S35 (48224)					
Patriot L/A																		
- Matte		650	35M (48500)	48483		40AM (48428)	616 (48319)	99474				S36 (48225)	S35 (48224)					
<b>MUSGRAVE</b>																		
Mark I & Mark II		54 (48054)	46 (48046)			402 (48108)						S54 (48230)	S46 (48227)	S402 (48247)				
Mark III & Mark IV		45 (48045)	46 (48046)			402 (48108)						S45 (48226)	S46 (48227)	S402 (48247)				
- Silver		45S (48510)	46S (48004)															
<b>NAVY ARMS</b>																		
Country Boy Muzzleloader		46 (48046)	46 (48046)		402 (48108)	402 (48108)	53 (48053)											
- Matte		46M (48502)	46M (48502)		402M (48429)	402M (48429)						S46 (48227)	S46 (48227)	S402 (48247)	S402 (48247)			
- Silver		46S (48004)	46S (48004)		402S (48430)	402S (48430)												
<b>NEW ENGLAND FIREARMS (H &amp; R)</b>																		
Handy Rifle Hornet (use Extra High rings)						82 (48082)												
N.E.F. 10 Gauge Shotgun		19 (48019)	19 (48019)															
Huntsman Muzzleloader	8					82 (48082)												
<b>NEW HAVEN</b>																		
495B (Matte)												10M (48416)						
<b>NORINCO</b>																		
22 Auto (Replica of Browning 22 Auto)	18					60A (48064)												
JW-15	12																	
<b>OCTAGON BARREL OR FLAT TOP RECEIVERS</b>																		
Can be fitted with the following bases:		61 (48061)	61 (48061)			50 (48050)												
<b>PARKER-HALE</b>																		
1000, 1000C, 1100, 1200 & 1700		45 (48045)	46 (48046)			402 (48108)						S45 (48226)	S46 (48227)	S402 (48247)				
- Silver		45S (48510)	46S (48004)			402S (48430)												
2600		71 (48071)	85 (48085)															
Midland		71 (48071)	75 (48075)															
<b>PEDER SOLI</b>																		
Lightning		75 (48075)	75 (48075)															
<b>PUMP SHOTGUNS</b>																		
All pumps EXCEPT Win. 42	4																	
<b>RAPTOR ARMS</b>																		
Same as Remington 700 Long Action	25	36 (48036)	35 (48035)			40A (48040)	98 (48098)					1 (48401)	S36 (48225)	S35 (48224)	S40A (48243)			

























B

799 (48010 is listed as inactive. We need if we want to have solution for 799 action)	71A (48010)	23 (48023)
---	-------------	------------

C

I've updated the mount chart removing the S47 (48228). Because of this there will be no Grand Slam option for the list of actions listed below.

Browning - A-Bolt, A-Bolt 22 Stalker and Medallion & BBR  
Cooey - 71  
Enfield - Winchester 70  
Marlin - MR7, XL7, XS7, X7  
Sears - 53  
Winchester - Model 70 Long Action, 670, 770, Model 70 Short Action 1984+

Redfield Steel Bases						
Gun	1 Piece Base		2 Piece Bases		2 Piece Extension Base	
	Black	Matte	Black	Matte	Black	Matte
<b>BROWNING</b>						
A-Bolt				47701		
A-Bolt III				47703		
X-Bolt				47707		
<b>DICKSON-HOWA</b>						
1500				47702		
<b>MOSSBERG</b>						
MVP				47702		
Patriot				47702		
<b>REMINGTON</b>						
700				47702		
783				47713		
7				47704		
<b>RUGER</b>						
American				47713		
<b>SAVAGE</b>						
10/110 Series				47713		
Axis Series				47713		
<b>Tika</b>						
T3				47726		
T3X				47726		
<b>WEATHERBY</b>						
Mark V				47714		
Vanguard				47727		
<b>WINCHESTER</b>						
70				47708		
XPR				47709		