

48328



TACTICAL PICATINNY SYSTEM

⚠ WARNING: UNLOAD FIREARMS BEFORE INSTALLATION TO PREVENT SHOOTING ACCIDENTS.

⚠ READ THOROUGHLY ALL DIRECTIONS AND SAFETY INSTRUCTIONS INCLUDED IN THIS PACKAGE. FAILURE TO COMPLY WILL RESULT IN AN UNSAFE FIREARM CONDITION THAT MAY CAUSE PROPERTY DAMAGE, PERSONAL INJURY OR DEATH.

ALWAYS FOLLOW THE RULES OF FIREARM SAFETY.

- **UNLOAD FIREARM, OPEN FIREARM ACTION AND ENGAGE FIREARM SAFETY BEFORE ATTACHING PICATINNY ADAPTOR. DO NOT REACH IN FRONT OF FIREARM MUZZLE TO MAKE ADJUSTMENTS OR MANIPULATE THE ADAPTOR.**
- **NOT ALL FIREARMS WILL FIT THE PICATINNY ADAPTOR PROPERLY DUE TO UNUSUAL FIREARM CONSTRUCTION AND THEREFORE SHOULD NOT BE USED.**
- **FAILURE TO COMPLY WILL RESULT IN AN UNSAFE FIREARM CONDITION THAT MAY CAUSE PROPERTY DAMAGE, PERSONAL INJURY OR DEATH.**

Installation Instructions:

For installation on most rifles with sling swivel studs.

1. Place rectangular Block #1 over the Swivel Stud on the firearm.
2. Insert Pin #2 through Block #1 and Swivel Stud.
3. Place Gasket #3 over Block #1.
4. Align holes in Rail #4 with tapped holes in Block #1.
5. Secure using Screws #5. Do not over tighten.

